GENERAL LIFE SAFETY NOTES

1. NO RATED WALLS EXIST IN AREA 'A' (OCCUPANCY A-3) OF THE MESHAW BUILDING. RECONFIGURED LOCKER AREA UTILIZES ONE EXISTING EXIT THROUGH INTERVENING SPACE OF THE FELLOWSHIP HALL WHICH MEETS REQMNTS OF NCSBC 1014.2.

2. EXIT SEPARATION SHALL BE 1/2 THE DIAGONAL DIMENSION OF THE FLOOR PLATE FOR THE FLOOR PER NCSBC SECTION 1015.2.1. THE EXITS SHOWN ARE EXISTING TO REMAIN.

3. FIRE EXTINGUISHER CABINETS SHOWN ARE NEW, EXISTING FIRE EXTINGUISHER CABINETS SHALL REMAIN.

4. G.C. TO COORDINATE INSTALLATION REQUIREMENTS OF EXIT SIGNS, ALL ASSOCIATED HARDWARE, JUNCTION BOXES, WIRING AND REQUIRED EXIT DEVICES W/ ELECTRICAL DRAWINGS AND LOCAL AHJ.

5. TOTAL OCCUPANCY FOR THE EXISTING MESHAW BUILDING REMAINS UNCHAGED BY THE ALTERNATE PLAN SHOWN.

LIFE SAFETY PLAN LEGEND

- SURFACE MOUNTED 10LB. ABC FIRE EXTINGUISHER CABINET. (ULINE 'H-4872' OR APPROVED EQUAL) PROVIDE RATED CABINET WHEN LOCATED IN A RATED WALL.

- **EXIT** — EXISTING EXTERIOR EXIT TO REMAIN

- **EXIT** — INDICATES ALTERED EXIT LOCATION, SEE ELECTRICAL DRAWINGS FOR EXIT SIGN LOCATION AND DIRECTION

- PATH 'A' — INDICATES EXIT TRAVEL DISTANCE

- ■ ■ ■ — 1 HOUR FIRE BARRIER - EXISTING TO REMAIN

- — ·· — 1 HOUR FIRE WALL - UL DESIGN NO. U305, WITH OPENINGS AS SCHEDULED (20 MIN.)

- ○○ — 2 HOUR FIRE WALL -EXISTING TO REMAIN

TRAVEL DISTANCES

PATH 'A'..153'-9"
PATH 'B'..88'-0"

*MAXIMUM EXIT ACCESS TRAVEL DISTANCE: E, A OCCUPANCY = 200'-0" (PER NCSBC TABLE 1016.1)

COMMON PATH DISTANCE

PATH 'A'............................(COMMON PATH HAS NOT BEEN ALTERED)

MESHAW BUILDING
FIRST FLR LIFE SAFETY PLAN (ALT.)

SCALE: 3/32" = 1'-0"

N

CONSULTANTS

RENOVATIONS TO

GRACE BAPTIST CHURCH

WILMINGTON
NORTH CAROLINA

HOSTETLER ARCHITECTURE STATE REGISTRATION
53256

ARCHITECT OF RECORD
SHAWN E. HOSTETLER
11926

CONSTRUCTION DOCUMENTS : 02.08.19

REVISIONS

MARK	DATE	DESCRIPTION
△		
△		
△		
△		

DRAWN BY: PROJ. MGR:

SHEET CONTENT

MESHAW BUILDING LIFE SAFETY PLAN (ALTERNATE)

JOB NO.	SHEET
18013	G101